



Tile Cleaner

Preparation, Application and Use guide

Preparation

Before using Tile Cleaner the area should be swept or vacuumed to remove all debris and detritus.

Conditions

Area must be free from ice and not subject to rain or water flow during application.

Mixing

Tile Cleaner should be diluted with clean hot or warm water.

Recommended dilution rates are:

Pre clean prior to treatment with Tile Profiler up to 50:1
General cleaning up to 100:1
Anti slip maintenance cleaning (post treatment) up to 50:1

Always add Tile Cleaner to the water and stir or mix lightly before application.

Application

Areas subjected to heavy staining or grease deposits can be spot treated with neat Tile Cleaner prior to application. Apply Tile Cleaner by squeegee or mop working well into all surfaces before rinsing with clean water.

When being used as a pre clean or anti slip maintenance cleaner Tile Cleaner should be allowed to stand before removing with clean water.

Recommended standing times are:

Pre clean minimum 15 minutes
Maintenance Cleaning up to 15 minutes

Should the areas anti slip properties be compromised they can be recovered by applying neat Tile Cleaner. After application allow to stand for 30 minutes before removing with clean water.

Subsequent Treatments

Once cleaned, the area can be treated with Merlin Coatings Tile Profiler to give a safe anti slip surface. Application can be performed whilst the surface is still wet.

Storage Conditions

Unless stated on the product technical data sheet all Merlin products have a shelf life of up to 2 years when stored in unopened containers with normal warehouse conditions.

Minimum storage temperature 5° Celsius
Do not expose to direct heat or sunlight
Do not allow to freeze