



# Tile Profiler

## Preparation, Application and Use guide

### Preparation

Before using Tile Profiler, the area should have been cleaned with Merlin Coatings Tile Cleaner and be free of all debris and detritus.

### Conditions

The area should be free from ice and not be subject to the possibility of rain or water flow until the application is completed.

### Mixing

Tile Cleaner is used as supplied. Shake container before use.

### Application

Before use a small test area should be performed to establish the required standing time for the particular type of tile to be treated.

Apply Tile Profiler by squeegee or mop working well into all surfaces at a rate of 10 square metres per kilo. Allow to stand for the required time before removing with clean water.

### Recommended standing time:

Ceramic tiles (high glaze)	up to 2 hours
Ceramic tiles (light texture)	up to 1 hour
Quarry tiles	up to 30 minutes
Quartz tiles	up to 45 minutes

### Subsequent Treatments

Once treated the anti slip qualities can be maintained with regular cleaning with Merlin Coatings Tile Cleaner.

### Storage Conditions

Unless stated on the product technical data sheet all Merlin products have a shelf life of up to 2 years when stored in unopened containers with normal warehouse conditions.

Minimum storage temperature 5° Celsius  
Do not expose to direct heat or sunlight  
Do not allow to freeze



IMPORTANT NOTICE: Except as provide by law, no liability shall be accepted for any loss, damage or consequential loss arising directly or indirectly from the use of the Companies products or information. As use of the products are beyond the companies control or knowledge, potential users should satisfy themselves by appropriate trials that the products are suitable and do not infringe on the rights of any third party. All materials are supplied subject to our conditions of sale, available on request.